



# Uzero clients



**N** CPU, Memory, OS, Drivers  
Software ,Storage, Data  
Moving Parts, Noise  
Heat Generation



**H** Security, Performance  
Reliability, Availability  
Resolutions upto 1920x1080  
Quality ABS Casing



**S** 40% on capex  
90% on opex  
90% on energy  
60% on upgradations









103 x 56 x 17.5 mm

# Technical Features

Device Type	Zero Client ( Connection to Server thru USB )
Configuration	Display Sharing Technology, VDS-Virtual Desktop Sharing
Supported Server OS	Windows Multipoint Server 2011 / 2012
Maximum Clients to Server	Up to 10*
I/O Ports	2 USB 2.0, 1 mini USB for Host Connection, Mic, Spk
Protocol Support	RDP 7.1 / 8.0
Native OS	No (Because it is Zero Client )
Remote Server Connectivity (Thru Internet)	No
Video Resolution	Upto 1680 * 1050
Audio Input	Yes
Audio Output	Yes
WireLess Option	No
Power Consumption	2 Watt
Dimensions	103mm X 56mm X 17.5mm
Weight	70 grams
Operating Temperature	Max 48 Degree Celsius
Placing Options	Desktop / Monitor Back
MTBF (Mean Time Before Failure)	4.9 Lack Hours

## Key Features

					
No Fan/s	Green PC	3 Years Warranty	No Noise	Advance Replacement	USB 2.0

## Technology Alliances

			
--	---	---	---

\*OS Licenses & Application software Licenses for Thin Client / Zero Clients may be required by the respective software vendors and must be purchased separately. Please read to the Microsoft operating System licensing requirements from the Microsoft website. Microsoft, Windows, Remote FX, Citrix, Citrix Ready, Linux, Intel, Atom, Arm are the registered trademark of their Respective Companies in Respective Countries. \* Depends on the RMA Inventory availability

Call for FREE DEMO  
**1800 200 2444**

**Authorized Partner:**